
ABI-EV1017

4 Channel RF PAL Modulator with infrared-bus

1) Description

Indoor RF Pal Modulator for Home & Small Office Networks based on Shielded Twisted Pair. DIN-Rail 35 mm compatible aluminium housing with 4 balanced composite video and audio input ports in RJ45 format. Provided with infrared-bus functionality.

- 2) Item Reference numbers
 - ABI-EV1017S00
- 4 Channel RF PAL Modulator with infrared-bus
- 3) General View



4) Picture



www.abitana.com

Author: Stefaan Dirix Pagina 1 040524_ABI_EV1017_DS_EN.doc

ABI-EV1017

4 Channel RF PAL Modulator with infrared-bus

- 5) Features: (Numbers refer to general view)
 - 1) F-type (IEC61169-24) single ended (Coax) UHF output (Dual-Side Band Carriers)
 - 2) Fully Shielded aluminium housing DIN-Rail (EN50022) compatible with fan-less cooling design.
 - 3) Low Power consuming design
 - 4) Power (5V) and Video Signal Indicator LED
 - 5) 4 Balanced inputs shielded RJ45 type (IEC60603-7) with:
 - Balanced Composite video on Pins 7&8
 - DC +5V on Pin 1 and GND on Pin 4
 - Infrared (5V pulsed) on Pin 5
 - Audio R on Pin 2 & Audio L on Pin 6 (Audio GND Pin 3)
 - 6) Raster selector and programmer
 - 7) Infrared Bus emitter and receiver at both sides
 - 8) Uses Comm. Center 5VDC power supply





Figure 1: Block Scheme

6) Typical Application:



www.abitana.com

Specification Sheet

ABI-EV1017

4 Channel RF PAL Modulator with infrared-bus

7) Technical characteristics

a. Mechanical

<u>Dimensions:</u> Height: 110mm Width: 71.2mm Depth: 65mm

Weight:: 190g

Connectors:

Output: F-Type IEC61169-24

• Input: RJ45 Shielded jacks IEC60603-7

Power: Phoenix Contact SMC 3.81

b. Electrical

Power supply Voltage: 5V DCPower Consumption: 1.2 W

• Ambient Operating Temperature: 0°C->40°C

c. Transmission

• 4 UHF output channels programmable between Channel 21 and 69

• Output level 72dBµV PAL G Modulation

• 16 MHz bandwidth/channel (min. separation)

d. Optical

Peak Wavelength of emission 880 nm

8) Package-Labeling

T.B.D.



Author: Stefaan Dirix Pagina 3 040524_ABI_EV1017_DS_EN.doc